

EVde-ROT 4 Series

Copper free Aluminium signaling fixtures with rotating light, painted RAL 6003, with 2 off M25 entries as standard. Evde-ROT-4 is available in the following colours: blue / orange / red / green / yellow / transparent.

Specifications

| | |
|-------------------------------------|--|
| Material | Copper-free aluminium (Cu <0.1%) |
| Temperature | -50°C to 60°C |
| IP Rating | IP65-66 |
| Approvals | INERIS 01ATEX0019X GOST Certificate |
| - Atex | |
| - GOST | |
| Standards | EN/IEC: 60079-0, 60079-1, 60079-7 EN: 61241-0, 61241-1 |
| Ex-code | Ⓔ II 2 GD Ex d IIC T5 / T4 Ex tD A21 IP65 T100°C / T135°C Ex de IIC T5 / T4 Ex tD A21 IP65 T100°C / T135°C |
| | According to European Directive 94/9/EC (ATEX) For Zone 1 & 2 and Zone 21 & 22 |
| Gaskets | O-ring made in Nitrile Rubber (NBR) |
| Surface treatment | External polyurethane painting (RAL 6003) |
| Entries | Nr. 2 M25 entries |
| Hardware and Screw | Stainless steel external hardware |
| Lamps | Lamp included |
| Lamps Wattage | 25W |
| Ballast | N.A. |
| Rated operation voltage (UE) | 12Vac / 24Vac / 48Vac / 110Vac / 230Vac / 240Vac 12Vdc / 24Vdc / 48Vdc |
| Frequency | 50/60 Hz |
| Accessories | Customized colours |
| Note | Continuous Running |



Signalling lighting fixtures with rotating light

| Type | Colour | Voltage | Dimensions | Weight kg | Power (W) |
|------------|-------------|-----------------|------------|-----------|-----------|
| EVde-ROT-4 | Transparent | 12V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Transparent | 24V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Transparent | 48V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Transparent | 12V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Transparent | 24V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Transparent | 48V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Transparent | 110V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Transparent | 230V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Transparent | 240V ac 50-60Hz | 220x516 | 8.500 | 25 |



STL International Ltd
Hill Farm, Linton Hill
Linton, Maidstone
Kent, ME17 4AL
United Kingdom
tel. +44 (0)1622 749633
fax. +44 (0)1622 746800
email. solutions@stl-int.co.uk
web. www.stl-int.co.uk



| Type | Colour | Voltage | Dimensions | Weight kg | Power (W) |
|------------|--------|-----------------|------------|-----------|-----------|
| EVde-ROT-4 | Blue | 12V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Blue | 24V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Blue | 48V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Blue | 12V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Blue | 24V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Blue | 48V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Blue | 110V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Blue | 230V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Blue | 240V ac 50-60Hz | 220x516 | 8.500 | 25 |

| Type | Colour | Voltage | Dimensions | Weight kg | Power (W) |
|------------|--------|-----------------|------------|-----------|-----------|
| EVde-ROT-4 | Orange | 12V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Orange | 24V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Orange | 48V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Orange | 12V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Orange | 24V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Orange | 48V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Orange | 110V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Orange | 230V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Orange | 240V ac 50-60Hz | 220x516 | 8.500 | 25 |

| Type | Colour | Voltage | Dimensions | Weight kg | Power (W) |
|------------|--------|-----------------|------------|-----------|-----------|
| EVde-ROT-4 | Red | 12V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Red | 24V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Red | 48V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Red | 12V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Red | 24V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Red | 48V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Red | 110V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Red | 230V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Red | 240V ac 50-60Hz | 220x516 | 8.500 | 25 |

| Type | Colour | Voltage | Dimensions | Weight kg | Power (W) |
|------------|--------|-----------------|------------|-----------|-----------|
| EVde-ROT-4 | Green | 12V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Green | 24V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Green | 48V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Green | 12V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Green | 24V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Green | 48V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Green | 110V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Green | 230V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Green | 240V ac 50-60Hz | 220x516 | 8.500 | 25 |

| Type | Colour | Voltage | Dimensions | Weight kg | Power (W) |
|------------|--------|-----------------|------------|-----------|-----------|
| EVde-ROT-4 | Yellow | 12V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Yellow | 24V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Yellow | 48V cc | 220x516 | 8.500 | 45 |
| EVde-ROT-4 | Yellow | 12V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Yellow | 24V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Yellow | 48V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Yellow | 110V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Yellow | 230V ac 50-60Hz | 220x516 | 8.500 | 25 |
| EVde-ROT-4 | Yellow | 240V ac 50-60Hz | 220x516 | 8.500 | 25 |